

Serial No. 09/977,757
Filed: October 15, 2001
Page 4 of 16

Examiner: Lilijana V. Ciric
Group Art Unit: 3743

BEST AVAILABLE COPY

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Previously presented) A method of operating a refrigerated oven to cook a food item therein, the refrigerated oven comprising a cooking chamber having a heating element for heating the cooking chamber, a refrigeration unit for cooling the cooking chamber, an insulated housing forming a refrigerated air path between the refrigeration unit and the cooking chamber, a temperature sensor for sensing the temperature of the cooking chamber, a data input device for inputting user-selected cooking cycle parameters, and a controller operably coupling the heating element, refrigeration unit, temperature sensor, and the data input device to selectively actuate the heating element and the refrigeration unit in response to the sensed temperature to implement the method as defined by the cooking cycle parameters, the method comprising the steps of:
 - A. producing cooled air in the refrigeration unit for a first period of time;
 - B. circulating the cooled air through the refrigerated air path to the cooking chamber to prevent spoilage of the food item;
 - C. heating the cooking chamber to cook the food item in the cooking chamber by cycling the heating element for a second time period; and
 - D. delaying the initiation of step A until the temperature of the cooking chamber cavity is below a predetermined threshold temperature.
2. (Original) The method of claim 1 wherein the predetermined threshold temperature is about 170 °F.
3. (Original) The method of claim 1 and further comprising terminating the operation of the refrigerated oven if the initiation of Step A is delayed beyond a predetermined time.
4. (Previously presented) The method of claim 1 wherein step B includes maintaining the temperature of the cooking chamber at a first predetermined temperature.

Serial No. 09/977,757
Filed: October 15, 2001
Page 5 of 16

Examiner: Lilijana V. Ciric
Group Art Unit: 3743

5. (Previously presented) The method of claim 1 wherein step C includes maintaining the temperature of the cooking chamber at a second predetermined temperature.

6. (Original) The method of claim 5 wherein the second predetermined temperature is inputted into the controller by a user.

7. (Original) The method of claim 1 and further comprising determining the first time period based on at least one cooking cycle parameter inputted by a user.

8. (Currently amended) The method of claim 1 wherein ~~there are two~~the cooking cycle parameters ~~based on input by a user, the~~comprise a first cooking cycle parameter being comprising an End Time corresponding to the time of day that step C is to be completed, and a second cooking cycle parameter being comprising a Bake Time corresponding to the length of time for cooking the food item, the termination of the first time period being determined by subtracting the Bake Time from the End Time.

9. (Original) The method of claim 8 wherein the second time period is equal to the Bake Time.

10. (Previously presented) The method of claim 1 and further comprising step:

E. after the completion of step C, heating the cooking chamber to maintain the food item at a temperature suitable for serving upon removal from the cooking chamber by cycling the heating element for a third time period.

11. (Previously presented) The method of claim 10 wherein step E is automatically initiated after step C.

12. (Previously presented) The method of claim 11 wherein step E is terminated upon the opening of the oven door.

13. (Previously presented) The method of claim 10 wherein step E includes maintaining the temperature of the cooking chamber at a third predetermined temperature.

14. (Previously presented) The method of claim 10 and further comprising the step of:

Serial No. 09/977,757
Filed: October 15, 2001
Page 6 of 16

Examiner: Lilijana V. Ciric
Group Art Unit: 3743

F. cooling the cooking chamber after step E to prevent the spoiling of the cooked food by cycling the refrigeration unit for a fourth time period.

15. (Previously presented) The method of claim 14 wherein step F is automatically initiated after step E.

16. (Previously presented) The method of claim 15 wherein step F is terminated upon the opening of the oven door

17. (Original) The method of claim 1 wherein step A is terminated if the cooking chamber is not reduced to a second predetermined threshold temperature within a predetermined time period.

18. (Original) The method of claim 17 wherein the second predetermined threshold temperature is 170°F.

19-37. (Canceled)

38. (Currently amended) A method of operating a refrigerated oven to cook a food item therein, the refrigerated oven comprising a cooking chamber having a heating element for heating the cooking chamber, a refrigeration unit for cooling the cooking chamber, a temperature sensor for sensing the temperature of the cooking chamber, a data input device for inputting user-selected cooking cycle parameters, and a controller operably coupling the heating element, refrigeration unit, temperature sensor, and the data input device to selectively actuate the heating element and the refrigeration unit in response to the sensed temperature to implement the method as defined by the cooking cycle parameters, the method comprising the steps of:

A. determining ~~first and second cooking cycle parameters based on input by a user; the~~ a first cycle parameter being comprising a Bake Time and corresponding to a length of time to cook a food item; the and a second cycle parameter being comprising an End Time corresponding to the time of day that heating of the cooking chamber in order to cook the food item in the cooking chamber is to be complete;

Serial No. 09/977,757
Filed: October 15, 2001
Page 7 of 16

Examiner: Lilijana V. Ciric
Group Art Unit: 3743

B. cooling the cooking chamber to prevent spoilage of the food item ~~in the~~ cooking chamber by cycling the refrigeration unit for a first time period determined by subtracting the Bake Time from the End Time;

C. heating the cooking chamber to cook the food item in the cooking chamber by cycling the heating element for a period of time corresponding to the Bake Time; and

D. delaying the initiation of step A until the temperature of the cooking chamber cavity is below a predetermined threshold temperature.